

Lafayette

(C) 2000-2021
By SMOOFV
21 years and counting...

Last modified 2020-11-09



Lafayette DC-24 AM/FM



www.rigpix.com



www.rigpix.com

SPECIFICATIONS

GENERAL

Type:	Citizen band transceiver
Frequency range:	26.965-27.255 MHz
Channels/tuning steps:	24 (1-23 + 11A)
Mode:	AM/FM
Frequency control:	PLL
Frequency stability:	? ppm
Power supply:	13.2 VDC (Nominal)
Current drain/power consumption:	RX: ? mA TX: ? A
Antenna impedance/connector:	50 ohm / TNC
Dimensions (W*H*D):	64*200*40 mm (2.52*7.87*1.58")
Weight:	575 g (1.27 lb), with rechargeable battery pack
Other features:	Dual watch. Backlit display.

RECEIVER SECTION

Receiver system:	? conversion superheterodyne 1st IF: ? MHz 2nd IF: ? KHz
Sensitivity:	
Selectivity:	
Image rejection:	
AF output power/speaker:	? mW at ?% distortion / ? ohm
External speaker connector:	

TRANSMITTER SECTION

RF output power:	AM Hi: 1 W, Lo: 300 mW FM Hi: 2 W, Lo: 300 mW
Modulation system:	
FM deviation:	±? KHz
Spurious emissions:	Less than -? dB
Microphone impedance/connector:	? ohm / ?-pin
Microphone input sensitivity:	? mV

MISCELLANEOUS

Manufactured:	1987-198x (Discontinued)
Main PCB:	
Additional info:	New price 1990 in Sweden: SEK 2630:-
Related documents:	
Sams Photofact #:	None
Modifications and fixes:	
Reviews:	

Options/Accessories:	? Rechargeable battery pack
	? Dry cell battery case. 9*LR6/AA batte
	? DC cable with cigarette lighter plug
	? Speaker-microphone