

7257

No. 1/5

Date

PARTS TABLE FOR SPOKEN 250

DESCRIPTION	SPECIFICATION	PCS/SET	NOTE 1	NOTE 2	NOTE 3
TRANSISTOR	MRF-454	2	MOTOROLA		
	2SC-2320-F	1	mitsubishi		
	A-733-R	1	NEC		
	D-359-E	2	mitsubishi		
	D-717	1	TOSHIBA		
	A-999	1	mitsubishi		
SCR	CRO2-AM2	1	mitsubishi		
DIODE	SR1DL-4R	1	mitsubishi		
	11R1SC	1	NEC		
	1N60	4	NEC		
	1S-1555	6	TOSHIBA		
	10D1	3	INTER		
ZENER	RE-13B	1	NEC		
LED	SEL-2110R	4	SANKEN		
	SEL-2310G	1	"		
SWITCH	ROTARY 1-3-4-20L	1	KOSHIGATA		
	TOGGLE TS-102	2	VIP		
	SS22-				
	SLIDE P-28K	1	WORLD		
	POWER STD-115A	1	SHINDEN		
RELAY	NTZTD-B	3	NAGANO		
CONNECTOR	NC-552-2	2	NANA		
RCA JACK	T-305	1	SANSEI		
FUSE HOLDER	FH-011B	1	ECHO		
FUSE	20A 6 ³ /30	1	SANSEI		
KNOB	B-25	1	HARUSAN		
SENSING COIL	CORE		TOMITA		
	WIRE 0.29x2x250				

DESCRIPTION	SPECIFICATION	PCS/SET	NOTE 1	NOTE 2	NOTE 3
HEATSINK	3D-007	1			
REAR PANEL	4D-007	1			
LAMP HOLDER	4D-006	1			
L - METAL	4D-001	2			
SUB PANEL	4D-005	1			
PANEL	4D-004	1			
COVER	3D-002	1			
BRACKET	3D-003	1			
INPUT TRANSFORMER	PCB 34 x 18	1			
	34 x 18	1			
	PIPE 70 x 19.5 x 6A	2			
	CORE TR 16 x 8 x 8	2	TOMITA		
OUTPUT TRANSFORMER	PCB 34 x 18	1			
	34 x 18	1			
	PIPE 70 x 29.5 x 6A	2			
	CORE TR 16 x 8 x 8	6	TOMITA		
RFC - 6H	VK-211	1	FERROXCUBE		
LOW-PASS COIL	0.3uH	2			
RFC - 3B	CORE RL 5.8-64-24	3	TOMITA		
RFC - 4B	CORE RL 5.8-64-24	4	TOMITA		
PCB	128 x 175	1			
	40 x 35	1			
	40 x 31	1			
	21 x 8	1			

DESCRIPTION	SPECIFICATION	PCS/SET	NOTE 1	NOTE 2	NOTE 3
POWER METER	SR-3600 1.2K Ω 200 μ A	1	TAKUMA		
METER LAMP	CT-33 18V	2	SANSEI		
RUBBER FOOT		4			
BUSH	8 ϕ 00	4			
CORD CLAMP	HP-4N	1	BURNDY		
POWER CORD	1015 AWG 14				
	1.2 m RED	1			
	1.2 m BLK	1			
COAXIAL CABLE	1.50-2V 120 ω /m	1			
	163 ω /m	1			
	286 ω /m	1			
CONTROL WIRE	1007 AWG 26				
	60 ω /m BLK	1			
	195 ω /m WH7	1			
	RED	1			
	YEL	1			
	230 ω /m ORG	1			
	VID	1			
	BLU	1			
	360 ω /m GRN	2			
	1007 AWG 22				
	130 ω /m RED	1			
	1015 AWG 18				
	40 ω /m RED	2			
	270 ω /m RED	1			
FB CABLE		1			
SIGNAL WIRE	NC	1			
	IN	1			
	OUT	1			

DESCRIPTION	SPECIFICATION	PCS/SET	NOTE 1	NOTE 2	NOTE 3
RESISTOR	SRD14R3 3.3 Ω	1	SHINRYU		
	100 Ω	2	"		
	270 Ω	1	"		
	1K Ω	10	"		
	3.3K Ω	3	"		
	4.7K Ω	1	"		
	10K Ω	3	"		
	39K Ω	1	"		
	47K Ω	3	"		
	56K Ω	1	"		
	SRD12PJ 10 Ω	4	"		
	27 Ω	1	"		
	RS-28 10 Ω	1	TDO		
	20 Ω	1	"		
	39 Ω	2	"		
	56 Ω	1	"		
	120 Ω	1	"		
	560 Ω	5	"		
	RS-28 100 Ω	2	"		
	W-5W 82 Ω	2	"		
CAPACITOR	CK 10pF				
	47pF				
	120pF				
	470pF				
	0.001 μ F				
	0.02 μ F				

DESCRIPTION	SPECIFICATION	Pcs/SET	NOTE 1	NOTE 2	NOTE 3
CAPACITOR	DM 18pF	3			
	50pF	2			
	82pF	2			
	100pF	3			
	180pF	2			
	200pF	1			
	470pF	1			
	560pF	1			
	1000pF	3			
	CE 0.47 μ F	2			
	2.2 μ F	1			
	33 μ F	2			
	100 μ F	3			
	330 μ F	1			
TRIMMER	10pF	1	TDO		
FIXED RT	RO-08FC-01 5KB	2	TECHNICA		
SCREW	BIS M3 x 4	1			
	x 5	11			
	x 8	9			
	WASHER SPRING M3	9			
	FLAT	1			
	NUT M3	4			
	LOG B3	1			
	COLOR 6-3-3	4			
	BIS M5 x 8	4			
	WASHER FLAT M5	4			
CHECK PIN		32			